

HOPPER

Width	1.83m (6')
Length	4.1m (13' 5")
Max volume (with extensions)	10m ³ (13yd ³)

FEEDER BELT

Width	1050mm (42")
Type	Plain belt
Control	Variable speed

VIBRATING GRID

Length	3.70m (12' 1")	
Width	2.0m (6' 7")	
Screen decks	Bofor Bars Punch Plate	Finger Tines Mesh

TIPPING GRID

Width	2.20m (7' 2")	
Length	4.95m (16' 2")	
Screen decks	Bofor bar	Mesh

MAIN BELT

Width	1050mm (42")
Control	Variable speed
Min discharge height	4.06m (13' 3")
Max discharge height	6.35m (20' 8")

POWERPACK

Type - ROW	JCB 444 dieselmax 63kW (84HP)
Type - EU	JCB 444 EcoMax 68kW (91HP)
Diesel tank	160L (35 gallon/42 US gallon)
Hydraulic tank	345L (76 gallon/91 US gallon)

TRACKS

Width	300mm
Speed	1km/h

**OPTIONS**

1. Radio remote tipping grid
2. Two-deck vibrating grid
3. Dust cover over main belt
5. Radio remote control
6. Deutz 3a TD2011 engine 49.4kw (66HP) - ROW
Deutz 3b TD2.9L4 Engine 50kw (67HP) - EU
7. Overband Magnet

PERFORMANCE

Max feed size	200mm
Capacity	up to 700 tph

WORKING DIMENSIONS

Length	17.30m (56' 11")
Width	2.25m (7' 4")
Height	6.58m (21' 6")

TRANSPORT DIMENSIONS

Length	11.90m (38' 11")
Width	2.25m (7' 4")
Height	2.50m (8' 4")

GENERAL

Weight		
Open Feed	13,300 kg	(14.7 US TON)
Tipping grid	15,000 kg	(16.55 US TON)
Vibrating grid	17,800 kg	(19.6 US TON)

ANACONDA[®]
CRUSH | SCREEN | STACK

Copyright 2014 by Anaconda Equipment International. All rights reserved
This document or any part thereof must not be reproduced without the permission of Anaconda